



SPECIFICATIONS	400 SERIES	400XL SERIES	500 SERIES	500XL SERIES
Maximum Round Bale Diameter	1.20m	1.20m	1.50m	1.50m
Maximum Rectangular Bale Size	N/A	1.20m x 0.90m	N/A	1.20m x 1.20m
Overall height (A)*	2.18m	2.53m	2.44m	2.80m
Overall Length (B)	2.36m	3.77m	2.36m	3.77m
Drum Diameter	1.57m	1.57m	1.83m	1.83m
Drum Length (standard)	1.55m	3.00m	1.55m	3.00m
Long Drum (optional)	1.85m	N/A	1.85m	N/A
Lower Chute discharge height*	0.40m	0.40m	0.40m	0.40m
Upper Chute discharge height*	1.14m	1.14m	1.14m	1.14m
PTO power required**	80HP	120HP	80HP	120HP

Mill (see page 3)	404M	404XLM	505M	505XLM
Transport width (C)***	1.91m	1.91m	2.01m	2.01m
Operating width (C)	3.13m	3.13m	3.13m	3.13m
Straw Giraffe discharge height*	1.84m	1.84m	1.84m	1.84m
Weight	904kg	1,168kg	970kg	1,259kg

Chop (see page 4)	4040	4040XL	5050	5050XL
Transport width (C)***	1.96m	1.96m	2.06m	2.06m
Operating width (C)****	2.32m	2.32m	2.42m	2.42m
Silage Giraffe discharge height*	1.53m	1.53m	1.53m	1.53m
Weight	811kg	1,075kg	877kg	1,166kg

Turbo Mill (see page 5)	T500BM	T500BXL
Overall Length (B)	2.56m	3.97m
Transport width (C) fan no RHC	2.51m	2.51m
Operating width (C) fan with RHC open	3.11m	3.11m
Weight	1390kg	1680kg

Key:

* Working heights will increase by up to 1m depending on tractor **Typical tractor size to provide adequate lifting capacity and stability

*** Chute extensions not fitted **** No optional left hand chute fitted